



Hydraulic Tools

MHP3 TracHorse

FEATURES:

- Self-Propelled - Mobile hydraulic tool and equipment carrier that transports tools and equipment in most job-site environments.
- Simple Operating Controls - Allows for a wide range of applications.
- Two Speed Forward Track Drive - Single Low Reverse Speed.
- Work Lights.
- Opening Tailgate.
- Auxiliary Hydraulic Tool Circuit - Is designed for continuous-duty applications and features the standard high-efficiency cooling found on all Stanley hydraulic power units.
- Climbs 60% grade.
- Carries 1,000 lbs / 454 kg.



SPECIFICATIONS:

MHP3	
Load Capacity	1000 lbs / 454 kg
Travel Speed	Low Speed 1.55 mph / 2.5 km/h High Speed 2.8 mph / 4.5 km/h
Weight	1125 lbs / 510 kg
Length	78 inches / 198 cm
Width	36 inches / 92 cm
Height	43 inches / 109 cm
Pressure	2000 psi / 38 bar
Flow Range:	
Twin Circuit	2 @ 5 gpm / 20 lpm or 1 @ 10 gpm / 38 lpm
Connect Size & Type	Flush-Face Couplers
Fuel Capacity	7 gallons / 26.5 liters
Hydraulic Capacity	3 gallons / 11 liters
Engines	Honda 20 hp OHV GX630

STANLEY

Hydraulic Tools

MHP3 TracHorse

ORDERING INFORMATION:

PART NUMBER	DESCRIPTION
MHP32242100	Twin Circuit, Honda Engine



WARRANTY:

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

Stanley Hydraulic Tools
3810 SE Naef Road
Milwaukie, OR 97267

503-659-5660
Fax 503-652-1780
stanley-hydraulic-tools.com