




LOCK
Enables quick opening and closing head.



XCG25

HYDRAULIC HEAD GUILLOTINE CABLES CUTTER



> Force, stroke, capacities same as the **CG25** manual tool and battery tools **BCE025G** & **BCL025G**.

TYPE OF CABLES
copper, aluminum and steel

MAX. PASSAGE
Ø 25 mm
(depending on cables)



- NEW REINFORCED BLADES**
Increase blades life time (> specifically for steel cuts).
- IDENTICAL BLADE & COUNTER BLADE**
Improve the cable cutting.
- INTERCHANGEABLE BLADES**
Easy to replace.

FORCE	55 kN
DIMENSIONS (L x l x h in mm)	215 x 52 x 90
WEIGHT (without protection kit)	2.400 kg

- PROTECTION KIT**
> As an option.
- FITTINGS & HOSES**
> Refer to **PAGE 67**.

	TYPE OF CABLES	MAX. HARDNESS	MAX. CUTTING Ø *
MULTI-STRAND CABLES	7 x 19 strands – steel	100 > 120 daN/mm ²	Ø 15 > 16 mm
	7 x 37 strands – steel	130 > 145 daN/mm ²	Ø 12 > 13 mm
ELECTRICAL CABLES	Bare – copper/aluminum		300 mm ²
	Rigid multi-strand – copper/aluminum		Ø 20 > 22 mm
	Semi-rigid multi-strand – copper/aluminum		
ROUND BARS	Copper	< 20 daN/mm ²	Ø 20 > 22 mm
	Hard copper	20 > 28 daN/mm ²	Ø 15 > 18 mm
	Aluminum	< 20 daN/mm ²	Ø 20 > 25 mm
	Mild steel	42 > 45 daN/mm ²	Ø 12 > 14 mm
	Medium hard steel	50 > 70 daN/mm ²	Ø 10 mm
INSULATED CABLES	Depends on the thickness of insulation		150 > 240 mm ²
	Stainless steel	< 150 daN/mm ²	Ø 8 > 10 mm

* Other dimensions and cables to be approved with tests.



Do not use this tool on live cables.