




**LOCK**  
Enables quick opening and closing head.







NEOELEC™  
**BCE025G**

HYDRAULIC CUTTING TOOL  
MINI PISTOL GUILLOTINE TYPE



> Identical force, stroke and capacities as the **CG25**, **XCG25** and the battery operated tool **BCL025G**.

-  **NEW REINFORCED BLADES**  
Increase blades life time (> especially for steel cuts).
-  **IDENTICAL BLADE & COUNTER BLADE**  
Improve the cable cutting.
-  **INTERCHANGEABLE BLADES**  
Easy to replace.
-  **ROTATIVE HEAD**  
180°

**TYPE OF CABLES**  
copper, aluminum and steel

**MAX. PASSAGE**  
**Ø 25 mm**  
(depending on cables)



<b>FORCE</b>	55 kN
<b>CUTTING TIME</b>	8 to 12 s
<b>CUTTING CAPACITY</b> – DEPENDS ON MATERIALS	
<b>DIMENSIONS</b> (L x l x h in mm)	300 x 75 x 280
<b>WEIGHT</b> (with battery)	3.400 kg

	TYPE OF CABLES	MAX. HARDNESS	MAX. CUTTING Ø *
<b>MULTI-STRAND CABLES</b>	7 x 19 strands – steel	100 > 120 daN/mm <sup>2</sup>	Ø 15 > 16 mm
	7 x 37 strands – steel	130 > 145 daN/mm <sup>2</sup>	Ø 12 > 13 mm
<b>ELECTRICAL CABLES</b>	Bare – copper/aluminum		300 mm <sup>2</sup>
	Rigid multi-strand – copper/aluminum		Ø 20 > 22 mm
	Semi-rigid multi-strand – copper/aluminum		
<b>ROUND BARS</b>	Copper	< 20 daN/mm <sup>2</sup>	Ø 20 > 22 mm
	Hard copper	20 > 28 daN/mm <sup>2</sup>	Ø 15 > 18 mm
	Aluminum	< 20 daN/mm <sup>2</sup>	Ø 20 > 25 mm
	Mild steel	42 > 45 daN/mm <sup>2</sup>	Ø 12 > 14 mm
	Medium hard steel	50 > 70 daN/mm <sup>2</sup>	Ø 10 mm
<b>INSULATED CABLES</b>	Depends on the thickness of insulation		150 > 240 mm <sup>2</sup>
	Stainless steel	< 150 daN/mm <sup>2</sup>	Ø 8 > 10 mm

\* Other dimensions and cables to be approved with tests.

 Do not use this tool on live cables.



<b>DIMENSIONS</b> (mm)	520 x 440 x 130
<b>WEIGHT</b>	2.300 kg

> Case and charger delivered with the tool.  
> NEOELEC™ accessories  
Refer to **PAGE 56 – 57**.

 **KW Hydraulik**  
Aggregate und Werkzeuge  
www.kw-hydraulik.de info@kw-hydraulik.de +49 3675 421 980