

Impact Wrench

IW12



SPECIFICATIONS

| ITEM | U.S.A. | METRIC |
|------------------------|--------------------------|-------------|
| Chuck Type – Sq. Drive | 3/4 in | 1.9 cm |
| Weight | 14 lb | 6.4 kg |
| Length | 9.5 in | 24.1 cm |
| Width | 4 in | 10.2 cm |
| Hydraulic Pressure | 1000-2000 psi | 70-140 bar |
| Torque | 250-1200 ft lb | 340-1632 Nm |
| Flow Range | 4-12 gpm | 15-45 lpm |
| Optimum Flow | 5-10 gpm | 20-38 lpm |
| Porting | -8 SAE O-ring | |
| Connect Size and Type | 3/8 in Male Pipe Adapter | |
| Motor | Integral | |

Stanley's hydraulic impact wrenches are used around the world by electric and gas utilities, construction crews, municipal agencies, and railroad crews.

No other tool, whether air or electric driven, can match the power, light weight and overall efficiency of our impact wrenches.

The **IW12** impact wrench features adjustable impact intensity. The **IW12** can handle a wide variety of applications.

The rugged Stanley impact wrench mechanism is simple to maintain and has many features to give it proven reliability. Torque transmission to the operator is minimal with the swing hammer design.

Designed to run from a wide range of hydraulic circuits, the **IW12** is used for nut, bolt and anchor bolt driving and is equally popular for wood boring and drilling.

The larger feathering trigger is convenient to use and gives the operator complete control of the wrench. The standard reversing valve provides instant reverse.

For operator comfort the **IW12** handle is coated with a heat insulating, shock absorbing material.

Underwater models available. Refer to ordering information.

ACCESSORIES

| ORDER NO. | DESCRIPTION |
|----------------|--|
| 02718 | Lubricant – Land Model 1 lb can |
| 03201 | Lubricant – Underwater Model 1 lb can |
| 01857 | Adjustable Chuck & Adapter – 3/4 in sq female x 3/4 in |
| 05117 | Adapter – 7/16 in hex x 1/2 in sq male |
| 05080 | Adapter – 5/8 in hex x 1/2 in sq male |
| 06790 | Adapter – 3/4 in sq anvil to 5/8 in hex |
| Sockets | Please refer to specification sheet 30097, Impact Wrench Sockets for IW12 / IW16, for available sockets and additional accessories. |

ORDERING INFORMATION

| ORDER NO. | DESCRIPTION |
|-----------|--|
| IW12140S | IW12 Impact Wrench – 3/4 in open center |
| IW340C | IW12 Underwater Impact Wrench – 3/4 in open center |

WARRANTY

Stanley Hydraulic Tools and their associated parts are warranted against defects in materials and workmanship for a period of twelve months from the date of purchase. Stanley Hydraulic Tools reserves the right to repair or replace only those parts which prove to have been defective at the time of purchase. This warranty becomes void if maximum flow and pressure ratings are exceeded.

All Stanley Hydraulic Tools, Parts, Accessories and allied equipment are subject to design improvements, specification and price changes at any time without notice and with no obligation to units already sold. Weights, dimensions and operating specifications listed herein are subject to change without notice. Where specifications are critical to your application, please consult Stanley Hydraulic Tools.

Call the Stanley Hydraulic Tools dealer nearest you...

**Stanley
Hydraulic Tools**

3810 SE Naef Road
Milwaukie, OR 97267-5698

Tel 503-659-5660
Fax 503-652-1780

STANLEY[®]

