
**GUIDING SHOE**


Avoids gap between blades.

# XCi95

## HYDRAULIC HEAD SCISSORS CABLES CUTTER

 700  
bar

**TYPE OF CABLES**  
copper and aluminum

**MAX. PASSAGE**  
Ø 95 mm

**ERGONOMIC HANDLE**

Easy to carry and for a secured tool handling.

<b>FORCE</b> (at piston)	130 kN
<b>FORCE</b> (between blades)	60 kN
<b>DIMENSIONS</b> (L x l x h in mm)	395 x 80 x 170
<b>WEIGHT</b> (without protection kit)	9.760 kg

**PROTECTION KIT**  
> As an option.

 **FITTINGS & HOSES**  
> Refer to **PAGE 67.**
**SCISSORS TYPE**  
Enables cable cuts in restricted areas  
(> direct access, without head closing).

 **REINFORCED & SHARPED BLADES**  
For mild steel reinforced cables in copper or aluminum cuts.

 **AS AN OPTION :**  
Earth grounding solution.  
> On demand.

**MAX. CUTTING CAPACITIES\***

<b>ALL THE MULTI STRAND CABLES IN ALUMINUM OR COPPER UP TO Ø 95 MM</b>	1200 mm <sup>2</sup>
<b>MILD STEEL REINFORCED CABLES IN ALUMINUM OR COPPER</b>	1000 mm <sup>2</sup>

\* Other dimensions and cables to be tested and validated.

Do not use this tool on live cables.