



LOCK
 Enables quick opening and closing head.



TYPE OF CABLES
 copper and aluminum

MAX. PASSAGE
 Ø 55 mm

NEOELEC™
BCP055G

HYDRAULIC CUTTING TOOL
PISTOL GUILLOTINE TYPE

18V
 4Ah

> Identical force, stroke and capacities as the **CG55 & XCG55**.



NEW COUNTER BLADE
 Decreases cable distortion when cutting.



SHARP BLADE & COUNTER BLADE
 Improve the cable cutting (> copper and aluminum cables).



ROTATIVE HEAD
 270°

FORCE	43 kN
CUTTING TIME	7 to 15 s
CUTTING CAPACITY – DEPENDS ON MATERIALS	
DIMENSIONS (L x l x h in mm)	500 x 75 x 335
WEIGHT (with battery)	6.400 kg



WIDE OPENING
 Easy for cables passage.



DIMENSIONS (mm)	594 x 494 x 149
WEIGHT	3.660 kg

> Case and charger delivered with the tool.
 > **NEOELEC™** accessories
 Refer to **PAGE 56 – 57**.

MAX. CUTTING CAPACITIES

* Other dimensions and cables to be approved with tests.

	TYPE OF CABLES	MAX. HARDNESS	SECTIONS	MAX. Ø OF CUT *
CABLES	Copper leads cables		4 x 185 mm ² or 630 mm ² max.	
	Underground aluminum		3 x 240 + 1 x 95 mm ²	Ø 51 mm
	Telephone cables			Ø 55 mm
BARS	Round annealed copper	< 20 daN/mm ²		Ø 16 – 18 mm
	Round annealed aluminum (A5)	< 16 daN/mm ²		Ø 20 – 25 mm



Do not use this tool on live cables.