




LOCK
Enables quick opening and closing head.



CG55





HYDRAULIC CUTTING TOOL MANUAL GUILLOTINE TYPE

> Identical force, stroke and capacities as the **XCG55** and the battery operated tool **BCP055G**.

TYPE OF CABLES
copper and aluminum

MAX. PASSAGE
Ø 55 mm



-  **NEW COUNTER BLADE**
Decreases cable distortion when cutting.
-  **SHARP BLADE & COUNTER BLADE**
Improve the cable cutting. (> copper and aluminum cables).
-  **LIGHT & STRONG TOOL**
Refer to the cutting capacities.
-  **2 SPEEDS HYDRAULIC SYSTEM**
For a fast advance.

FORCE	43 kN
DIMENSIONS (L x l x h in mm)	560 x 55 x 140
WEIGHT	3.700 kg



WIDE OPENING
Easy for cables passage.



CANVAS BAG – Delivered with the tool.

MAX. CUTTING CAPACITIES

* Other dimensions and cables to be approved with tests.

	TYPE OF CABLES	MAX. HARDNESS	SECTIONS	MAX. Ø OF CUT *
CABLES	Copper leads cables		4 x 185 mm ² or 630 mm ² max.	
	Underground aluminum		3 x 240 + 1 x 95 mm ²	Ø 51 mm
	Telephone cables			Ø 55 mm
BARs	Round annealed copper	< 20 daN/mm ²		Ø 16 – 18 mm
	Round annealed aluminum (A5)	< 16 daN/mm ²		Ø 20 – 25 mm



Do not use this tool on live cables.



www.kw-hydraulik.de info@kw-hydraulik.de +49 3675 421 980

www.dubuis.com