

# KW Hydraulik GmbH

Kabelwerkzeuge und Werkzeuge für die Montage und Demontage



## RAPTOR DIESEL

### HYDRAULIC POWER PACK 20 - 30 L/min 140 Bar



Professional power pack with Diesel engine HATZ 10,5 HP - recoil and battery start.

The pack gives flows from 20 to 30 L/min and 140 Bar pressure to power tools of group C and D of EHTMA standard.

Every part of **RAPTOR DIESEL** is manufactured to give the maximum of performances, reliability and transportability. The points of strength are the quietness the robustness and economy that make its use ideal in the urban maintenance and in the professional works in general.

The new design and the numerous exclusive features make point by point **RAPTOR DIESEL** one of the best products available today on the market.

**NOTE** the hydraulic power can be different and supplied according to customer specifications

### ADVANTAGES

- ROBUST FRAME IN STAINLESS STEEL TUBE WITH BENDABLE LIFTING EYE
- QUICK COUPLERS INSTALLED ON SWIVEL FITTINGS PROTECT AGAINST IMPACTS
- OIL COOLER INSTALLED ON SUCTION LINE AVOIDS DAMAGEFUL PRESSURE PULSATIONS
- HIGH EFFICIENCY OIL TEMPERATURE CONTROL IDEAL FOR TROPICAL CLIMATES
- ENGINE AND HYDRAULIC PARTS INSTALLED FLOATING ON SHOCK MOUNTS TO LIMIT NOISE AND VIBRATIONS
- NOISE ABSORBING PANELS, SUPERIOR AND LATERAL, ASSURE ALSO PROTECTION AGAINST IMPACTS
- LARGE PNEUMATIC WHEELS FOR EASY MOVEMENT ON ROUGH TERRAINS

### ENGINE CHARACTERISTICS

ENGINE TYPE	<b>HATZ DIESEL</b>
POWER	<b>10,5 HP</b>
STARTING	<b>RECOIL AND BATTERY</b>
ENGINE ACCELERATION	<b>MANUAL</b>
BATTERY POWER	<b>30 Ampere</b>

### WEIGHT AND DIMENSION

WEIGHT WITH LIQUIDS	<b>135 Kg</b>
HEIGHT	<b>70 cm</b>
LENGHT	<b>88 cm</b>
WIDTH	<b>65 cm</b>

### HYDRAULIC CHARACTERISTICS

FLOW	<b>20 - 30 l/min</b>
PRESSURE MAX	<b>140 BAR</b>
OIL TANK CAPACITY	<b>12 L</b>
STD HOSE LENGTH	<b>7 mt</b>